

Specifications	Opera 100 Color ID Card Printer
Print Speed	Downloads and prints a full color edge-to-edge image in 30 seconds. Downloads and prints a monochrome card in 6 seconds.
Duty Cycle	Continuous
Security Features	Standard Holokote anti-copying watermark across entire face of card. When used with Holopatch™ cards one area of the Holokote® watermark is highlighted as a high visibility security seal.
Warranty	12 months limited warranty.
Data Interface to PC	USB rev1.1 (USB 2.0 compatible)
Supplied Software	Windows 98, ME, 2000, XP drivers Magicard ID badging package
Consumables	Opera Consumables
Dyefilm Setup	Automatic
Printhead	300dpi field replaceable
Magstripe Encoder	None
Power Source	External power "brick" for 90-265V 40-60Hz (autoranging)
Dimensions	6.9in wide x 7.8in high x 8.3 in deep. (175mm x 200mm x 211mm)
Weight	7lb (3.2Kg) approx.
Color	Metallic Silver/Translucent Red
Operating Environment	Sheltered Office environment 50°F to 85°F (10°C to 30°C)
Safety	CE certified, UL listing pending
EMC	EN50 081-1 and EN 50 082-1 (Europe) FCC pt15 curveA (USA) and CSA 08.8 curve A (Canada)
	Opera 105 Color ID Card Printer with built in HiCo Magstripe Encoder
Print Speed	Downloads and prints a full color edge-to-edge image and magnetically encodes and verifies tracks 1 and 2 in around 35 seconds